



VS

V91 HDD MAX

Hard drive degausser and Tape eraser

FEATURES

- High energy degausser for hard drives & magnetic tape
- 7,000 gauss field strength
- Less than 12 seconds for complete erasure
- Cost effective



OUR PROMISE

- Three Year Warranty, extendable on request
- Lifetime Technical Support
- A trusted brand - Innovators and manufacturers of data destroyer solutions for over 30 years



U.S. 530-626-6924

U.K. +44 (0) 1252 333577

info@vssecurityproducts.com

veritysystems.com



INTRODUCTION

The **V91 HDD Max** is a second generation, high energy degausser especially designed for the complete erasure of today's high coercivity hard drives and tapes.

High Energy: With an effective field strength of up to 7,000 gauss - the **V91 HDD Max** is particularly recommended for erasing hard disk drives with high density coercivity levels. With figures in excess of -75dB for high energy metal tapes and up to -90dB on standard oxide tapes, complete erasure is assured every time with quick erasure times running as little as 12 seconds per cassette.

Powerful enough to erase data hard drives, DLT, SDLT, 3480's and more - the **V91 HDD Max** is a compact, low noise, manually operated unit that sits neatly on a table top.

Why Degauss Hard Drives?

The only way to safeguard complete and permanent erasure is to use a degausser. Although in most cases this will render the hard drive inoperative, the cost of a replacement hard drive cannot be compared to the cost to a company if sensitive information can be read by a third party.



Make the V91 HDD Max part of your data security policy

U.S. 530-626-6924

info@vssecurityproducts.com

veritysystems.com



U.K. +44 (0) 1252 333577

SPECIFICATIONS

Media Handling:

Standard PC, Laptop and Server 3.5", 2.5" & 1.8" Hard Drives.

Longitudinal & perpendicular recording, up to 2TB.

All drive interfaces; IDE, SATA and Fibre Channel.

All backup tapes including; DLT,2,3,4,5,6 & SDLT, LTO1,2,3,4,5,6,7 & 8 3480/3490/3490e,3590,9840,T9940 & T10000 tape.

Ultrium & Redwood SD-3 tape and cartridges.

Mammoth 1 & 2, 8mm, AIT1 & 2, M2 tapes, DDS 1,2,3,4 & 5, DD-2

Other Media Erased:

½" Computer tape & Diskettes (Single or Boxed), DC 600, 2000

TK50, 70, 85, 4mm, 8mm, Exabyte, Travan, DAT & ZIP disk

HD cam, SR, VHS, SVHS, U-Matic, Betacam & Digital Betacam SP

MIII, D1,2,3,4 & 5, DVC Pro, Hi-8 & Mini DV, 1" Tape on reels.

Power Supply: 208-220v 60Hz, 220-240v 50Hz

Current Rating: 60Hz 12 Amps, 50Hz 10 Amps typical.

(Please specify Voltage and Frequency when ordering)



Degaussing Force: 7,000 Gauss

Erasure Depth: -75dB on 1500 OE tape, -90dB on 750 OE tape

Duty Cycle: 20%

Dimensions (WxHxD): 16.5" x 6" x 19" (42cm x 48cm x 36cm)

Unit Weight: 64lbs (29kg)

Packed Dimensions

(WxHxD): 19.5" x 29.1" x 19.5" (50cm x 74cm x 50cm)

Packed Weight: 75lbs (34kg)

Throughput: 200 hard drives in one continuous session. Up to 275 hard drives in the first hour.

Controls: On/Off Power switch. Reset Button

Indicators: Liquid Crystal Display (LCD)

Warranty: 24 Months back to base, all parts & labour included. Extended warranties also available.

U.S. 530-626-6924

U.K. +44 (0) 1252 333577

info@vssecurityproducts.com

veritysystems.com



WHO RECOMMENDS HARD DRIVE DEGAUSSING?

As part of their guidelines for sanitization of magnetic media, **degaussing** is recommended by:

- National Institute of Standards & Technology
- Department of Defence
- Government Security Organizations

The following **Government Mandates** require destruction of sensitive information stored on Hard Drives and Tapes before disposal:

- PCI DSS (Payment Card Industry)
- Data Security Standard
- PIPEDA (Personal Information Protection and Electronic Document Act)
- NIST (National Institute of Standards and Technology)
- Guidelines for Media Sanitization
- NIST SP 800-88 & NIST SP 800-36
- Gramm-Leach-Bliley Act (GLBA)
- HIPAA (Health Information Portability and Accountability Act)
- California SB-1386
- IRS-1075
- CJIS
- Bank Secrecy Act (BSA)
- GDPR (General Data Protection Regulation)

VS Security Products maintains a policy of continuous improvement and reserves the right to amend this specification without notice.

Tailored Transport Case:

For transporting the Degausser, or for safe storage when not in use, we have designed a case with convenient handle and wheels.



U.S. 530-626-6924

U.K. +44 (0) 1252 333577

info@vssecurityproducts.com

veritysystems.com

